



SERIES 2010

DISPERSER, POST MOUNTED, VARIABLE HIGH SPEED, HIGH TORQUE, MECHANICAL DRIVE, CONTROL BOX

MODEL DVH-200-60/29-C-EX-/SS

Standard Features:

- Motor, 20 HP, 1,750 rpm, 3-phase, 60 Hz, 230/460V, TEFC (explosion proof), High efficiency
- Fixed center single belt drive, easy to change belt
- Mixing shaft (SS304), polished, speed range 650 to 3,000 rpm, nominal
- Air-over-oil lift, 60" rise, with lift controls (3way air valve, muffler, air pressure relief valve, foot valve), non-foaming hydraulic oil
- High speed blade, high shear, type HSF-12 (12" dia.), 12" from floor
- Side mounted speed control with hand wheel
- Manual head lock with torque arm
- Height limitation safety limit switch, explosion proof (wired in series with on/off push button)
- Can lock, adjustable, up to 200 gallon vessel
- Can lock limit switch, explosion proof, wired in series with on/off push button

Control Box, with

• Motor starter, with heaters, on/off button, Ebutton, digital ammeter, digital tachometer, internal wired, ready to be wired at site.

This disperser has all the standard features needed for safe, efficient, and economic operation. This unit is ready to be wired in a 460 volt control room bus



DANTCO MIXERS CORPORATION
9 OAK STREET
PATERSON, NJ 07501-3013
973-278-8776, FAX 973-278-1538
EMAIL sales@dantco.com, WEB http://www.dantco.com