



SERIES 3021 MIXER, BLENDER, AGITATOR, FIXED LOW SPEED, MOUNTED ON MIXING TANK

MIXER MODEL FSB-300-84-EX/SS TANK MODEL TFD-5K-96/96-SS

Features, as shown: Mixer:

- Motor 30 HP, 1750 rpm,
 3-phase, 60 Hz, 230/460V,
 explosion proof, Class 1, Group D,
 Div. 1
- Gear reducer, SEW, in line, ratio 24:1, service factor (SF) 1.9
- Mixing shaft speed, 74 rpm, nominal
- Mixing shaft, 3 ½" dia. SS304
- Top turbine and mid turbine 52" dia, 4 blade, type AFF (axial flow, down push)
- Bottom turbine, 60" diameter, 3blade, type VHE (very high efficiency, down push, axial flow)

Mixing Tank:

- Diameter, 96", Straight Section, 96"
- Bottom flanged and dished (F&D)
- Tank Cover, fixed one side, hinged fron side, 8" collar, 3" FNPT
- Baffle, 6" wide, 4 required
- Legs, struct. stl, W8-30, 24" from floor
- Working capacity, 4500 gallon, weight, empty, 6000 lbs



DANTCO MIXERS CORPORATION
9 OAK STREET
PATERSON, NJ 07501-3013
973-278-8776, FAX 973-278-1538
EMAIL sales@dantco.com, WEB http://www.dantco.com