



## **SERIES 2010**

### **DISPERSER POST MOUNTED, VARIABLE HIGH SPEED, HIGH TORQUE, CONTROL BOX**

#### **MODEL DVH-200-53/26-C-TEFC/SS**

##### **Standard Features:**

- Motor, 20 HP, 1750 rpm, 3-phase, 60 Hz, 230V, TEFC (non explosion proof), high efficiency.
- Fixed center single belt drive, easy to change belt
- Mixing shaft (SS304), polished, speed range 650 to 3,000 rpm, nominal
- Air-over-oil lift, 53" rise, with lift controls (3-way air valve, mipler, air pressure relief valve, foot val), non foaming hydraulic oil
- High speed blade, high shear, type HSF-12 (12" dia., 8" from floor)
- Side mounted speed control with hand wheel
- Speed indicator (approximate speed)
- Manual head lock with torque arm
- Height limitation safety limit switch, non explosion proof (wired in series with on/off push button)
- Can lock limit switch, non explosion proof, wired in series with other limit switch and in series with on/off push button



##### **Control Box, with**

- Motor starter with heaters, on/off, e-Switch, digital ammeter, digital tachometer, internal wired, ready to be wired at site

This disperser has all the standard features needed for safe, efficient, and economic operation.

This unit is ready to be wired in a 230 Volt control room bus



**DANTCO MIXERS CORPORATION**  
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL [sales@dantco.com](mailto:sales@dantco.com), WEB <http://www.dantco.com>