



SERIES 2005

DISPERSER, LAB/PILOT, BENCH TOP, MEDIUM HIGH SPEED, MODERATE TORQUE

MODEL DVW-010-19/4.5-EX/SS

Features, as shown:

- Motor, 1 HP, 1750 rpm, 3-phase, 60 Hz, 203V, 145T frame, explosion proof, Class 1, Group. D, Div.1
- Variable pitch pulley and belt drive
- Variable speed range, 385 to 1157 rpm, nominal (other ranges are available)
- Front speed control
- Speed indicator on side by motor
- Lift, hydraulic jack, manual, 18" rise
- Can lock, chain, adjustable up to 5 gallon
- Mixing shaft, 7/8" diameter by 15" long
- High shear blades, 2", 3" & 4"
- Height 43" raised, 31" lowered
- Throat, 4 ½", nominal
- Foot print 16" by 25", nominal
- Power input, 3-phase, 60 Hz, 220V
- Suitable for bench operation

Special Features (optional):

- Tachometer, analog, installed
- Ammeter in explosion proof enclosure, analog
- Motor starter in explosion proof enclosure
- Motor/starter/ammeter wiring, humidity tight, 6 foot cord (no plug)
- Mixing vessels on wheels, plain or jacketed
- Mixing pails, plain or jacketed

Other bench top models are available with 2 or 3 HP motors, explosion proof or TEFC only.

DANTCO MIXERS CORPORATION
9 OAK STREET
PATERSON, NJ 07501-3013
973-278-8776, FAX 973-278-1538
EMAIL sales@dantco.com, WEB http://www.dantco.com