



SERIES 508
LAB/PILOT MIXER (PASTE)
VARIABLE LOW SPEED
AC MOTOR & VFI CONTROLLER

MODEL: DVL-100-18/7-TEFC/SS

Special Features, as shown:

- 1 HP motor, TEFC, inverter duty
- In-Power: 10A, 220V, 60 Hz, single phase
- Keypad to control and display speed
- Mixing shaft speed range: 10 to 200 rpm
- 11" diameter, 3-blade, Butterfly Turbine
- Lift, manual, hydraulic jack, 15" rise
- Can Lock, Chain, Binder, adjustable
- Plate Stand, 24" x 13", Retort Bar (optional)
- Suitable for bench top operation, 5 gallon pail shown
- Power cord, 6 foot, plug optional

Options (not shown):

- Explosion proof version
- Pneumatic Lift & Controls, 18" rise, 6" throat
- Filter-Lubricator-Regulator for air lift
- Chuck, 3/4", at mixing shaft
- Other types of Turbines

These units may be available in post mounted configuration with air over oil lift in sizes up to 5 HP (explosion proof or non explosion proof).

Input power to units with 1/2 HP and 1 HP motors may be single phase, either 110V or 220V. Input power to units with 1 1/2 HP motors and up is single phase, 220V.

Price list shows price of units with standard features and options for special units.



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>