



SERIES 2002

DISPERSER, LAB/PILOT, POST MOUNTED, EXPLOSION PROOF VARIABLE HIGH SPEED

MODEL DVH-020A00-20/9-EX/SS

Features, as shown:

- Motor, 2 HP, 3-phase, 60 HZ, 230/460V, 1750 rpm, 145T, TEFC/EX
- Variable pitch pulleys & belt drive
- Variable speed range 430 to 4100 rpm, nominal
- Speed control knob, top of motor
- Air-over-oil lift with controls, 18" rise
- Can lock, heavy duty, with chain and binder, adjustable from 2 gallon to 18 gallon container (not shown)
- Lift limit switch for safety, expl. proof
- Mixing shaft, 7/8" bu 16" long
- High shear blades, 2", 3" 4" and 6"
- Tachometer, analog, installed
- Ammeter, 0 to 10 amps range, analog, in explosion proof enclosure, installed
- Motor starter with heaters & on/off/resetd, in expl. proof enclosure
- Motor/starter/ammeter wiring, humidity tight, 6 foot cord (no plug)
- Power input, 3phase, 60 Hz, 220V (420V input is available on request)
- Suitable for floor operation

Options:

- Side or front speed control
- Mixing vessels on wheels, plain or jacketed
- Limit switch on can lock, expl. proof



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>