



SERIES 5004GA AIR MIXER/DISPERSER DRUM LID BUNG ENTERING

MODEL DBE-150-BGA

- Variable Speed
- Heavy duty with advanced adapter
- Standard torque
- Mixing/Dispersing application

STANDARD FEATURES

- $1 \frac{1}{2}$ HP @ top speed
- 100 to 3000 rpm, nominal
- 5/8" or 3/4" mixing shaft, SS304
- 3" to 6" high shear blades with hub
- Needle valve for speed control
- Silencer at air exhaust.

OPTIONAL ACCESSORIES

- Drum cover, CS or SS
- 3/8" air line and connectors
- Filter regulator lubricator (FRL)
- Sanitary plated finish

This bung entering air mixer model is screwed into the 2" NPT bung opening of the closed drum for quick and easy mounting on standard steel drums. The special threaded adapter allows the mixing shaft to be at an angle toward the center of the drum for optimum mixing. The standard folding impeller is SS304folds for entry sd opens to 6" diameter when mixing. The impeller comes with a hub that allows adjustment anywhere on the mixing shaft. Additional impellerswith various opening diamteters are available. This model is equipped with a 1 ½ HP air motor with a useable variable speed range of 300 to 3000 rpm.



DANTCO MIXERS CORPORATION
9 OAK STREET
PATERSON, NJ 07501-3013
973-278-8776, FAX 973-278-1538
EMAIL sales@dantco.com, WEB http://www.dantco.com