



SERIES 3021 MIXER, BLENDER, AGITATOR, FIXED LOW SPEED, MOUNTED ON MIXING TANK, MIXER, MODEL FSB-150-84-EX/SS TANK, MODEL TFD-2250-84/96-SS

Features, as shown:

Mixer:

- Motor 15 HP, 1750 rpm, 254TC frame, 3-phase, 60 Hz, 230/460V, explosion proof, Class 1, Group D, Div. 1
- Gear reducer, SEW, in line, ratio 24:1, service factor (SF) 1.9
- Mixing shaft speed, 43 rpm, nominal
- Mixing shaft, 2 1/2" diameter, SS304
- Mid turbine, 40" diameter, 4-blade, type AFF (axial flow, down push)
- Bottom turbine, 52" diameter, 3-blade, type VHE (very high efficiency, down push, axial flow)

Mixing Tank:

- Diameter, 84"; Straight Section, 96"
- Bottom, flanged & dished (F&D)
- Tank Cover, fixed one side, hinged Front side
- Baffles, 6" wide, 4 required
- Legs, struct. stl, W6-20, 24" from floor
- Working capacity, 2000 gallon Weight, empty: 4000 lbs.



DANTCO MIXERS CORPORATION
9 OAK STREET
PATERSON, NJ 07501-3013
973-278-8776, FAX 973-278-1538
EMAIL sales@dantco.com, WEB http://www.dantco.com