



## TANK/DISPERSER ASSEMBLY MODEL DAC200T04WSB230GCS

### DISPERSER, SERIES 3002, FIXED SPEED, MODEL DAC-200-36-TEFC/SS

- Motor, 20 HP, 1750 rpm, 256TC frame, 3-phase, 60 Hz, 230/460V, TEFC (non explosion proof)
- Materials, carbon steel
- Bearing housing, 10" diameter pipe, machined
- Motor/Mixing Shaft rigid coupling, flanged, bolted and keyed
- Outboard bearing, flanged
- Mixing shaft, 2" dia, SS304, 36" long below the flange
- Mixing shaft lip seal
- Mixing shaft speed, 180 to 1800 rpm (with VFD drive by others)
- Blade assembly, 12" style HSG, blade holders 6" diameter, collar, bolt and lock washer, all in SS304
- Mounting flange, 8" ANCI, 14" diameter,
- Bridge, 10" channel, bolted to tank ring

### MIXING TANK, MODEL TO4W-LT-SB-230G-CS

- Materials, carbon steel
- Diameter, 40" ID, Depth:42"
- Thermowell coupling, 1" FNPT
- Top ring, 2"x 2" x 1/4" angle
- Bottom, 2" slope to 2" FNPT drain
- Lift tubes, 3 x 7 " , carbon steel, 28" center
- Casters, swivel, 4" poly
- Cover, 1/3 hinged, shoe box lid, handle
- Tank Handles, 2 required
- Finish, inside, all welds ground smooth
- Finish, outside, painted grey enamel
- Working capacity, 230 gallon
- Max capacity, Lineal capacity,



DANTCO MIXERS CORPORATION  
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL [sales@dantco.com](mailto:sales@dantco.com), WEB <http://www.dantco.com>