



TANK/MIXER ASSEMBLY MODEL DTE03TO4WSB230CS

MIXER, SERIES 5016 MODEL DTE-03-340-TEFC/SS304

- Motor, 3 HP, 3/60/240V, TEFC (non explosion proof)
- Reducer, SEW, in line, hollow bore, 5 to 1 ratio
- Mixing shaft, 1 1/2" diameter, SS304
15 degrees inclined to achieve figure 8 flow
- Turbine, 14" diameter, 3 blade, very high efficiency (style VHE), 2 set screws, SS304
- Motor/Reducer bracket weldment, bolted to top ring, carbon steel
- Mixing shaft speed, 50 to 340 rpm, (with VFD Drive supplied by others)

MIXING TANK MODEL TO4W-LT-SB-230G-CS



- Materials, carbon steel
- Diameter, 40" ID
- Depth, 42"
- Sloping bottom, 2" to FNPT 2" drain
- Thermowell coupling, 1" FNPT
- Top ring, 2"x2"x1/4" angle
- Lift tubes, 7"x3"
- Casters, swivel, 4" poly
- Tank handles, 2 required
- Cover, 1/3 hinged, 1" lip, handle
- Paint, outside surfaces, gray enamel, sprayed
- All internal welds ground smooth
- Working Capacity: 230 gallon
- Max. Capacity: Lineal Capacity:



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>