



KETTLE, PROCESS, SANITARY
F&D BOTTOM,
HEATING & COOLING,
SIDEJACKET, 75 PSIG

MODEL TO4W-10G-75J-BF-SS316
MODEL TO4W-15G-75J-BF-SS316
MODEL TO4W-20G-75J-BF-SS316

10 gallon, working capacity
15 gallon, working capacity
20 gallon, working capacity



Features:

- Materials: SS 316L
- Inner shell diameter: 14", 18", 20"
- Outer shell diameter: 16", 20", 22"
- Straight section: 16", 17", 20"
- Bottom, Flanged & dished (F&D)
- Jacket inlet & outlet: 1/2", ferrules.
- Drain: 3/4", ferrule. Legs 1 1/2" tubing
- Cover, hinged, with 3 inlet ferrules
- Baffles, internal, 4 req'd, bolted and removable.. Mixer mount bracket
- Swivel casters, nylon wheels, 3" dia
- Inside finish, 150 grits, sanitary
- Outside finish, 120 grit



Other components available:

- Mixers, dispersers, air or electric
- Thermo probe and temperature display
- High speed blade, low speed turbine



Applications:

- Pilot disperser, high speed
- Mixers, low speed
- Pilot mills



DANTCO MIXERS CORPORATION
9 OAK STREET
PATERSON, NJ 07501-3013
973-278-8776, FAX 973-278-1538
EMAIL sales@dantco.com, WEB <http://www.dantco.com>