



**CHILLER, PAIL/KETTLE
STANDARD 5 GALLON PAIL INSERT
SHELL JACKET, 75 PSIG MAX.
INTERNAL SHELL TAPERED,
FLAT BOTTOM**

MODEL TFDU-5G-MP-75SS

Scope:

To process products in standard 5 gallon metal pails when inserted in the kettle to the pail first rim.

Inner shell is slightly tapered for ease pail release.

Features:

- Materials: SS304
- Inner tapered shell top diameter: 11 1/4"
- Packet jacket diameter: 14" (no taper)
- Depth 9 1/2" to hold 5 gallon pail at the first rim
- Bottom: flat
- Flat bottom clearance: 1"
- Jacket inlet/outlet: 3/8" FNPT (back side)
- Drain: none
- Side handles: 2 required
- Legs: 4 req'd, 1 1/4" tubing, welded to bottom
- Leg pads: 2 1/2" square
- Inside finish: 120 grit
- Outside finish: 120 grit

Applications:

- Heating, cooling, chilling products inserts, typically 5 gallon standard metal pails
- Inks, adhesives, food products, flavor/fragrances, cosmetics.



DANTCO MIXERS CORPORATION
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>