



**KETTLE, PROCESS, SANITARY
15 DEGREES CONE
HEATING/COOLING
SIDE & CONE JACKET, 75 PSIG**

MODEL TO4W-10G-75J-SS316

**10 GALLON WORKING CAPACITY
12 GALLON MAXIMUM CAPACITY**

Features:

- Materials: SS316 (SS304 jacket)
- Inner shell diameter: 14"
- Outer shell diameter: 16"
- Straight section: 16"
- Bottom cone: 1 1/2", 15 degrees
- Jacket inlet & outlet: 3/8" FNPT
- Drain, 1 1/2" flush ball valve with drain ferrule, manual
- Drain clearance: 12"
- Top recess for cover: 1/4"
- Cover, hinged, shaft entry slot with cover: 15 3/4" OD
- Legs, 4 required: 1 1/2" tubing
- Leg pads: 3" x 4" x 3/16"
- Inside finish: 150 grits
- Outside finish: 120 grits

Other components available:

- Mixers, dispersers, air or electric motors
- Thermo probe and temperature display
- High speed blades, low speed turbines (axial flow, radial flow, bow tie, butterfly, 2-blade anchor, etc.)

Applications:

- Pilot dispersers, high speed
- Mixers, low speed
- Pilot mills



**DANTCO MIXERS CORPORATION
9 OAK STREET**

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL sales@dantco.com, WEB <http://www.dantco.com>