



**PAIL/KETTLE, CHILLER,  
STANDARD 5 GALLON PAIL INSERT,  
HEATING/COOLING/CHILLING,  
FLAT BOTTOM,  
INTERNAL SHELL SLIGHTLY SLOPED,  
SHELL JACKET, 75 PSIG , MAX.**

**MODEL TFDU-5G-H-S-75/SS**

**Scope:**

To process products in standard 5 gallon pails when inserted in the kettle to the pail first rim. Inner shell is lightly tapered for ease of pail release.

**Features:**

- Materials SS304
- Inner shell sloped, top diameter, 11 1/4"
- Pocket jacket diameter, 14"
  - o Depth, 9 1/2" to hold 5 gallon pail at the rim
- Bottom, flat
- Jacket inlet/outlet 3/8" FNPT (dark side)
- Drain, none; flat bottom clearance: 1"
  - o Side handles, 2 required
- Legs, 4 required 1 1/4" tubing
- Leg pads 3" x 3"
- Inside finish 150 grit
- Outside finish 150 grits

**Other components available:**

- Covers
- Mixers, air or electric motors
- Thermo Probe and Temperature Display
- Other materials including SS316

**APPLICATION:**

- Heating, cooling, chilling products in inserts, typically 5 gallon standard pails
- Inks, adhesives, food products, flavor/fragrance, cosmetics



DANTCO MIXERS CORPORATION  
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL [sales@dantco.com](mailto:sales@dantco.com), WEB <http://www.dantco.com>