



## PAIL, PROCESS, SANITARY, FLAT BOTTOM

### Standard Specifications:

- Bottom radius: ½"
- Top flange: 3/8" to ½"
- Handles: as required
- Spout, 2" wide: as required
- Cover: as required
- Drain, bottom flush: as required
- Construction: heavy gage
- Materials: SS304 or 316
- Finish, inside: 240 grits

### *Top 2 pictures, left to right:*

#### Model PP-5G-SS

- Working capacity: 5 gal
- Inner diameter: 11 ½"
- Depth: 13"

#### Model PP-3G-SS

- Working capacity: 3 gal
- Inner diameter: 9"
- Depth: 11"

#### Model PP-2G-SS

- Working capacity: 2 gal
- Inner diameter: 8"
- Depth: 10"

### *Bottom picture:*

#### Model PP-15G-SS

- Working capacity: 15gal
- Inner diameter: 16"
- Depth: 18"

Other models available are from ½ liter (1/4 qt) to 2000 liters (500 gal).

The large diameter units may be suitable for skid transport.

Integral dolly on SS casters with choice of wheels may be added.



DANTCO MIXERS CORPORATION  
9 OAK STREET

PATERSON, NJ 07501-3013

973-278-8776, FAX 973-278-1538

EMAIL [sales@dantco.com](mailto:sales@dantco.com), WEB <http://www.dantco.com>